

DS-PWA64-L-WB AX PRO

AX PRO supports Wi-Fi, TCP/IP, and GPRS communication methods. It also supports ISAPI, Hik-Connect, and DC-09, which is applicable to the scenarios of market, store, house, factory, warehouse, office, etc.



Key Feature

- TCP/IP, Wi-Fi, and GPRS network
- New generation wireless protocol: Tri-X/Cam-X
- Long RF transmission distance
- Two-way communication with AES-128 encryption
- Connects up to 64 wireless zones/outputs, 32 wireless keyfobs, 2 repeaters, 4 sounders, 8 tag readers & keypads, and PIRCAM.
- Supports up to 32 network users, including 1 installer, 1 administrator, and 30 normal users.
- Voice prompt
- Configuration via Web client, mobile client, and Convergence Cloud
- Hik-Connect and Hik-ProConnect configuration depends on the user access level
- Pushes alarm notification via messages or phone calls
- Views live videos from Hik-Connect
- Uploads alarm reports to ARC
- Supports LED indicator to indicates system status
- 4520 mAh lithium backup battery
- SIA-DC09 protocol, and supports both Contact ID and SIA data format

Available Model

- DS-PWA64-L-WB (433MHz)



Specification

AX PRO L		
Basic	Frequency	433Mhz
	Wireless type	2-way wireless
	Wireless Security	Frequency Hoping 128 AES Encryption
	Wireless Zones	Up to 64
	Wireless Outputs	
	Wireless Tag Readers & Keypads	Up to 8
	Wireless Sounders	4
	Wireless Keyfobs	32
	Wireless Repeaters	2
	Tags	32
	PIRCAM	Supported
User	Installer	1
	Admin	1
	Users	30
Key Software Features	Areas	16
	Voice prompt	Supported
	Loudspeaker built in	Supported
	LEDs Status	Arm/Disarm, Alarm, Tamper, Fault, Cloud, Power
	Memory Log stored	5000
	RS-232 output	Supported
	Programming tools	Hik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence Cloud
	Firmware upgrade	APP Manual
	Arm Modes	Away/Stay
	Automatic Arm/Disarm Timers	Supported
	Forced Arming with Open Zones	Supported
	Diagnostics of via the APP or Web	Supported
Communication	LAN port	Supported
	Wi-Fi on board	Supported(2.4G)
	GPRS on board	Supported
	SIM slot	Single
	SMS notification	Supported
	Alarm voice call	Supported
	ARC protocol	SIA DC09(SIA level 2, Contact ID), ISUP, ISAPI (SDK)

	User APP for operating	Supported
	Installer APP for programming	Supported
	Web server for maintenance (offline configuration)	Supported
Hardware	Battery Stand by	12 hours
	Power Supply	Built in power supply
	Battery pack	Built in on board Battery Li
	Housing	Plastic
Automation	Schedules	Wall switch & Relay & Plug (Has time schedule)
Approvals	FCC	Supported
	CE/CB	Supported
	RCM	Supported
	Rohs/Reach/WEEE	Supported
Others	Operation temperature	-10 °C to +55 °C
	Dimension(W x H x D)	170.0 mm (6.7") x 170.0 (6.7") mm x 38.6 mm (1.5")
	Weight	557.5 g(19.7 oz)

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
sateru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com